

Yale hoists and trolleys are not designed for passenger elevation applications and must not be used for this purpose.

UNOplus-A ATEX Ratchet lever hoist

Capacity 750 - 6000 kg

The UNOplus - Series A ratchet lever hoist is the result of further technical development of the UNOplus, which has proven itself over many years.

The versatile tool for lifting, pulling and securing of loads is characterised by its compact design, robust stamped steel construction and the smoothly running free chaining device. The further reduced weight optimizes operation, makes the application even more comfortable and the UNOplus -Series A to a convenient, versatile device.

Benefits & features


- Due to optimized gearing and improved bearings in the housing cover a minimum effort is required to operate the short hand lever.
- Impact resistant stamped steel frame and gear cover withstands repeated rigorous use.
- Closed load chain guide prevent accidentally slipping out.
- · Increased corrosion protection through zinc-plated and yellow-chromated chain guide, chain stripper and parts of the brake.
- Guide, chain stripper and parts of the brake with corrosion-protected components.
- · Alloyed steel link chain in accordance with national and international standards and regulations.
- Bolt on hooks with nyloc nuts simplify the inspection process. Hooks are forged, allowing them to yield under overload without breaking.


Technical data UNOplus-A ATEX BASIC II 3G Ex h IIA T4 Gc / II 3D Ex h IIIA T135°C Dc / Mining I M2 Ex h Mb

Model	Item-No.	Capacity in kg/ number of chain falls	Chain dimensions dxp mm	Load chain grade	Lift with one full lever turn mm	Handle pull at WLL daN	Weight at standard lift (1.5 m) kg
UNOplus-A ATEX 750	192049841	750/1	5.6 x 17.1	T	27	22	6.3
UNOplus-A ATEX 1500	192049940	1500/1	7.1 x 21	Ţ	22	35	9.2
UNOplus-A ATEX 3000	192050025	3000/1	10 x 28	T	20	40	16.9
UNOplus-A ATEX 6000	192050579	6000/2	10 x 28	T	10	43	28.6

Dimensions UNOplus-A ATEX

Model	UNOplus-A ATEX 750	UNOplus-A ATEX 1500	UNOplus-A ATEX 3000	UNOplus-A ATEX 6000
A min., mm	312	375	445	563
B, mm	20	26	37	45
C, mm	27	31	40	47
D, mm	18	21	28	35
E, mm	267	267	376	376
F, mm	121	146	180	232
G, mm	40	51	57	71
H, mm	81	95	123	161
J, mm	144	164	193	193
K, mm	53	68	83	83
L. mm	91	96	110	110





UNOplus-A ATEX 1500